

A09 Typ 324-50 Kurzkegelflansch für ISO 702-1 (DIN 55026), beidseitig fertig bearbeitet (ohne Befestigungsschrauben)

Id.-Nr.	Ø A mm	Kegel	B mm	C mm	D mm	E mm	F mm	G	H mm	I	J mm
176804 ▲	125	3	17	102	53.975	51.2	70,6	3xø10,5	95	3x M8	108
176805 ▲	125	4	17	117	63.513	60.7	82,6	3x ø11	95	3x M8	108
176806 ▲	125	5	17	146	82.563	79.4	104,8	3x ø11	95	3x M8	108
176807 ▲	160	4	22	117	63.513	60.7	82,6	3x ø11	125	3x M10	140
176809 ▲	200	4	22.5	117	63.513	60.7	82,6	3x ø11	160	3x M10	176
176810 ▲	200	5	22.5	146	82.563	79.4	104,8	3x ø11	160	3x M10	176
176811 ▲	200	6	21.5	181	106.375	103	133,4	4x ø14	160	3x M10	176
176812 ▲	200	8	27	210	139.719	136	171,4	3x ø18	160	3x M10	176
176813 ▲	250	5	21	146	82.563	79.4	104,8	4x ø11	200	3x M12	224
176814 ▲	250	6	26	181	106.375	103	133,4	4x ø14	200	3x M12	224
176815 ▲	250	8	26	225	139.719	136	171,4	4x ø18	200	3x M12	224
176816 ▲	315	6	31.5	181	106.375	103	133,4	4x ø14	260	3x M12	286
176817 ▲	315	8	31	225	139.719	136	171,4	4x ø18	260	3x M12	286
176818 ▲	315	11	31	298	196.869	192.7	235	6x ø22	260	3x M12	286
176819 ▲	400	6	32.5	181	106.375	103	133,4	4x ø14	330	3x M16	362
176820 ▲	400	8	32	225	139.719	136	171,4	4x ø18	330	3x M16	362
176821 ▲	400	11	32.5	298	196.869	192.7	235	6x ø22	330	3x M16	362
176822 ▲	400	15	36	380	285.775	281.2	330,2	6x ø26	330	3x M16	362
176823 ▲	500	8	36	225	139.719	136	171,4	4x ø18	420	6x M16	458
176824 ▲	500	11	36	298	196.869	192.7	235	6x ø22	420	6x M16	458
176825 ▲	500	15	36	380	285.775	281.2	330,2	6x ø26	420	6x M16	458
176826 ▲	630	11	39	298	196.869	192.7	235	6x ø22	545	6x M16	586
176827 ▲	630	15	39	403	285.775	281.2	330,2	6x ø26	545	6x M16	586
159883 ▲	630	20	42	520	412.775	407.5	463,6	6x ø26	545	6x M16	586

