

# Slim - extended centre point



## APPLICATION

For counter-clamping workpieces on turning and grinding machines. Especially suited for cramped work area between centre point and workpiece as well as low-lying workpiece centres.

## TYPE



Compact design with minimum casing diameter.  
With extended centre point.

## CUSTOMER BENEFITS

- Enlarged work area and better workpiece accessibility thanks to narrow casing diameter and extended centre point
- Maximum rigidity at high speeds thanks to compact design
- Maximum concentricity deviation of 0.008 mm for maximum precision

## TECHNICAL FEATURES

- Body hardened and ground
- Tip angle 60°



A06 Slim with small casing diameter and extended centre point body hardened and ground - tip angle 60°

Item no.	362080	362081	362082	362083	362084
Mount MT	2	3	4	5	6
Size	02	04	08	10	14
A mm	73	74	88.5	119	164
B mm	32	34	42	58	80
D mm	15	15	20	30	42
G mm	17.78	23.825	31.267	44.399	63.348
K mm	29.5	32	37.5	51.5	70.5
J mm	10	11	13	14	18
Weight approx. g	320	460	1000	2600	7100
Workpiece weight max. kg	170	340	700	1400	3000
Concentricity deviation max. mm	0.008	0.008	0.008	0.01	0.02
Speed max. min <sup>-1</sup>	7000	7000	6300	4300	3000
Spare live centres	1241753	1241754	1241755	1241756	1241757